

# ISOLI

## CLAIER

# PNT 205N

کلایر، نماینده انحصاری ایزولی در ایران



Altezza max. di lavoro  
Max. Working height  
Max. Arbeitshöhe

20 m

Sbraccio max. di lavoro  
Max. Working boom extension  
Max. Arbeitsaulandung

9.10 m ca.

Portata  
Capacity  
Tragfähigkeit

230 Kg

N° operatori  
N° operators  
N° de Arbeiter

2

Forza manuale max.  
Max. manual force  
Max. Handkraft

40 daN

Velocità max. vento  
Max. wind speed  
Max. Windgeschwindigkeit

12.5 m/s

Braccio di lavoro  
Working boom  
Arbeitsarm

Doppio Pantografo + Braccio telescopico

α 2 sezioni

Double pantograph + telescopic end 2  
section element

Angolo braccio  
Boom angle  
Armwinkel

-20°/+80°

Rotazione sovrastruttura  
Upperstructure rotation  
550°

Piattaforma  
Platform  
Hubarbeitsbühne  
Alluminio 1400x710x1115 mm  
Aluminium 1400x710x1115 mm

Rotazione piattaforma  
Platform rotation  
Drehung des Hubarbeitsbühne  
Idraulica 90°dx+ 90°sx  
Hydraulic 90°RH+ 90°LH

Livellamento piattaforma  
Platform levelling  
Nivellierung der Hubarbeitsbühne  
Idraulico  
Hydraulic

Stabilizzatori  
Outriggers  
Abstützungen  
Idraulici, inclinati ant./post.  
Hydraulic, "A" type at front/rear

Scartamento minimo stab.  
Outriggers minimum width  
Spurweite Abstützungen min./max.  
Anteriore 2.77 m - Posteriore 2.80 m  
Front 2.77 m - Rear 2.80 m

Comandi  
Controls  
Steuerungen  
Elettroidraulici  
Electro-hydraulic

Installazione minima  
Minimum installation  
Mindeste Installation  
MTT 3.5 t  
TWG 3.5 t

