

ISOLI

CLAIER

PT 160

کلایر، نماینده انحصاری ایزولی در ایران



Altezza max. di lavoro
Max. Working height
Max. Arbeitshöhe
16m

Sbraccio max. di lavoro
Max. Working boom extension
Max. Arbeitsaulandung
8,9 m H+H

Portata
Capacity
Tragfähigkeit
max 250 kg

N° operatori
N° operators
N° de Arbeiter
2

Forza manuale max.
Max. manual force
Max. Handkraft
40 daN

Velocità max. vento
Max. wind speed
Max. Windgeschwindigkeit
12.5 m/s

Braccio di lavoro
Working boom
Arbeitsarm
Braccio telescopico a 3 sezioni
Telescopic end 3 section element

Angolo braccio
Boom angle
Armwinkel
-25°/+75°

Rotazione sovrastruttura
Upperstructure rotation
400°

Piattaforma
Platform
Hubarbeitsbühne
Alluminio 1390x715x1115 mm
Alluminium 1390x715x1115 mm

Rotazione piattaforma
Platform rotation
Drehung des Hubarbeitsbühne
Idraulica 90°dx+ 90°sx
Hydraulic 90°RH+ 90°LH

Livellamento piattaforma
Platform levelling
Nivellierung der Hubarbeitsbühne
Idraulico
Hydraulic


Stabilizzatori
Outriggers
Abstützungen


Idraulici, verticali ant./post.
Hydraulic, "H" type at front/rear


Scartamento minimo stab.
Outriggers minimum width
Spurweite Abstützungen min./max.
Anteriore 1.95 m - Posteriore 2.01 m
Front 1.95 m - Rear 2.01 m

Comandi
Controls
Steuerungen
Idraulici
Hydraulic

Installazione minima
Minimum installation
Mindeste Installation
MTT 3.5 t
TWG 3.5 t

A= 
MAX
250 kg

C= 
MAX
120 kg

B= 
MAX
200 kg

D= 
MAX
80 kg

